



Unidrive Rubber Mixing Mill

- Unidrive Mixing Mill with Anti friction Roller Bearing with Helical Gear Box of Greaves / Elecon / Shanti Make.
- Unidrive Mixing Mill Bush type with Helical Gear Box of Greaves / Elecon / Shanti.

Technical Specifications for Unidrive Mixing Mill

Specification	RMMUA-12	RMMUA-14	RMMUA-16	RMMUA-18	RMMUA-22	RMMUA-26
Batch Capacity (Approx.)	15-20 Kgs.	25-30 Kgs.	35-40 Kgs.	40-50 Kgs.	60-80 Kgs.	90-110 Kgs.
Power (H.P.)	30	40	60	75	125	250
Roll Size	12"Øx 30" L	14"Ø x 36" L	16"Ø x 42" L	18"Ø x 48" L	22"Ø x 60" L	26"Ø x 84" L
Friction Ratio	1:1.18 to 1:1.22	1:1.18 to 1:1.22	1:1.18 to 1:1.22	1:1.18 to 1:1.22	1:1.18 to 1:1.22	1:1.18 to 1:1.22
Lubrication Pump (Grease)	Manual	Manual	Radial	Radial	Radial	Radial
Roll Cooling / Heating	Universal Rotary Joint	Universal Rotary Joint	Universal Rotary Joint	Universal Rotary Joint	Universal Rotary Joint	Universal Rotary Joint
Nip Adjustment	Centralized Manual	Centralized Manual	Centralized Manual	Motorized	Motorized	Motorized
Electrical Panel	Optional	Optional	Optional	Auto Reversal Panel	Auto Reversal Panel	Auto Reversal Panel
Emergency Brakes	Optional	Optional	Optional	Hydraulic Thruster Brake	Hydraulic Thruster Brake	Hydraulic Thruster Brake
Approx. Weight (Tons)	4-4.5	5.5-6	8.5-9	11-11.5	18-18.5	25-25.5
Dimension (Ft.) LxBxH	8.5 x 3.5 x 5.5	12 x 4.5 x 6.5	13 x 6.5 x 7.5	14.5 x 7.5 x 8.5	15.5 x 8.5 x 9	16.5 x 9.5 x 10

CONTACT US

Ravi Engineering Works, New Delhi

Contact Person

Mr. Sachin Sethi

Address

29/19, Street No. 6,
Anand Parbat Industrial Area
New Delhi - 110 005 (India)

Tel. :

+ (91)-(11)-55489741/55489742/28715517/28717282

Fax :

+ (91)-(11)-25731310/28714369

E-mail :

ravieng@vsnl.com
sales@rubbermachineries.com
purchase@rubbermachineries.com